



# Patch panel, 24 ports RJ45, unloaded



## Standards of reference and applications

EIA19"

## Installation Features

**Store at** -0 to +70 °C

**Install at** -0 to +50 °C

**Operate at** : -20 to +60 °C

**Fitting** : designed for unshielded and shielded LAN 1 unit EIA 19" rack mount.

## Design

**Material** : black powder painted steel (front), galvanised steel (rear).

**Features** : built-in cable holder rack with cable shield termination.

**Printing :** Numbered 1-24

**Size :** 18.4 x 38.4 x 25.7 mm, 1 Unit

## Ordering and delivery information

Ports	P/N	Size [mm]	Weight [kg/km]	Packaging
24	PPE24SU	18.4H x 38.4W x 25.7D	1.0	1 pc/box

## Recommended connectivity

**Keystone jack :** all APS Keystone Jacks Category 5e, 6, 6A.

**Patchcords :** PCMJ6U\_, PCMJ6F\_, PCMJ6S\_.

## Extended System Warranty

The APS System Warranty assures the compliance of the system performance to the applicable class of cabling for a period of 25 years. The warranty may be applied for by an accredited APS Partner who has designed and/or installed the entire system.



**Every effort has been put so that this document is most reliable and free from errors. However, AP Solutions Oy cannot be considered responsible for any mistake in this document and users should consult AP Solutions Oy for any information needed. AP Solutions Oy reserves the right to make changes to the documents at any time, without prior notice.**